

**The Invention Claimed Is:**

1. A computer system comprising:  
a base;  
a frame hingedly mounted on the base to pivot between open positions  
and a closed position; and  
5 a display rotatably mounted in the frame to rotate between an inward  
facing position and an outward facing position.
2. A computer system as defined in claim 1 wherein:  
the computer system can convertibly serve as a notebook personal  
computer and a tablet personal computer.
3. A computer system as defined in claim 1 wherein:  
a viewing side of the display faces toward the base when the display is  
in the inward facing position and the frame is in the closed position.
4. A computer system as defined in claim 1 wherein:  
a viewing side of the display faces away from the base when the display  
is in the outward facing position and the frame is in the closed position.
5. A computer system as defined in claim 1 further comprising:  
an antenna disposed in the frame and operable to emit a signal  
substantially in a predetermined direction relative to the frame regardless of whether  
the display is in either one of the inward facing position and the outward facing  
5 position.
6. A computer system as defined in claim 5 wherein:  
the frame has an outward side that faces away from the base;  
the signal is emitted away from the outward side of the frame when the  
frame is in any one of the open positions and the closed position and the display is in  
5 either one of the inward facing position and the outward facing position.
7. A computer system as defined in claim 1 further comprising:  
control buttons disposed in the display and user accessible when the  
frame is in the open position and the display is in the inward facing position and when  
the frame is in the closed position and the display is in the outward facing position.
8. A computer system as defined in claim 1 wherein:  
the display has a perimeter; and  
the frame substantially surrounds the perimeter of the display.

9. A computer system as defined in claim 1 wherein:  
the display rotates about a horizontal axis relative to the frame.

10. A computer system comprising:  
a base;  
a display holder pivotally mounted on the base;  
a display rotatably mounted on the display holder; and  
first and second hinges on opposite edges of the display connecting the

display to the display holder.

11. A computer system as defined in claim 10 wherein:  
the display has a top edge, a bottom edge and two opposing side edges;

and

the first and second hinges are disposed on the two opposing side  
edges of the display.

12. A computer system as defined in claim 10 wherein:  
the display has a top edge, a bottom edge and two opposing side edges;

and

the first and second hinges are disposed on the top edge and the bottom  
edge, respectively, of the display.

13. A computer system comprising:

a base;

a display holder mounted on the base;

a display mounted about the display holder and having two opposing  
edges and an electrical connection disposed near each opposing edge; and

two electrical paths, each connecting one of the electrical connections of  
the display through the display holder to the base.

14. A computer system as defined in claim 13 further comprising:

first and second clutch interfaces pivotally connecting the base and the  
display holder; and

first and second hinges rotatably connecting the display holder and the  
display at the two opposing edges;

and wherein:

a first one of the electrical paths passes through the first hinge and the  
first clutch interface between a first one of the opposing edges of the display and the  
base; and

- 10                   a second one of the electrical paths passes through the second hinge  
and the second clutch interface between a second one of the opposing edges of the  
display and the base.
15.     A computer system comprising:  
          a base; and  
          a display mounted about the base with first and second axes of rotation  
relative to the base, the first axis of rotation being proximate to and substantially  
5     parallel to an edge of the display and pivoting the display between pivoted positions,  
and the second axis of rotation being proximate to and substantially parallel to a  
centerline of the display regardless of the pivoted position of the display.
16.     A computer system as defined in claim 15 wherein:  
          the second axis of rotation is along a horizontal centerline of the display  
extending between opposite edges of the display.
17.     A computer system as defined in claim 15 wherein:  
          the second axis of rotation is along a vertical centerline of the display  
extending between a top and a bottom of the display.
18.     A display section for a hybrid notebook/tablet computer system having a  
base, comprising:  
          a frame; and  
          a display rotatably mounted in the frame to rotate between first and  
5     second positions relative to the frame;  
          and wherein the frame is capable of being pivotally mounted to the base  
of the hybrid notebook/tablet computer system.
19.     A display section as defined in claim 18 wherein:  
          the frame has an inward side and an outward side;  
          the display has a viewing side;  
          in the first position of the display relative to the frame, the viewing side of  
5     the display is proximate to the inward side of the frame; and  
          in the second position of the display relative to the frame, the viewing  
side of the display is proximate to the outward side of the frame.
20.     A display section as defined in claim 19 wherein:  
          the first position of the display relative to the frame enables the hybrid  
notebook/tablet computer system to serve as a notebook personal computer upon  
mounting the display section to the base; and

- 5                   the second position of the display relative to the frame enables the hybrid notebook/tablet computer system to serve as a tablet personal computer upon mounting the display section to the base.
21.    A display section as defined in claim 18 further comprising:  
          an antenna disposed in the frame and, upon operation, emitting a signal substantially in a predetermined direction relative to the frame when the display is in either one of the first and second positions.
22.    A display section as defined in claim 18 further comprising:  
          control buttons disposed in the display;  
          and wherein:  
          the display has a viewing side; and  
5           the control buttons are accessible on the viewing side of the display.
23.    A display section as defined in claim 18 wherein:  
          the display has a perimeter; and  
          the frame substantially surrounds the perimeter of the display.
24.    A display section as defined in claim 18 wherein:  
          the display rotates about a horizontal axis relative to the frame.
25.    A method of using a computer system comprising:  
          providing the computer system with a display section closed against a base, the display section having a frame and a display within the frame;  
          opening the display section by pivoting the frame away from the base;  
5           rotating the display from a first position to a second position relative to the frame; and  
          closing the display section by pivoting the frame toward the base.